

List of Tables

CHAPTER III	Pages
Structural Characterization of CdSe Thin Films	68-113
3.1 X-ray diffractogram data of bulk Cadmium Selenide sample	79
3.2 d_{hkl} values of CdSe sample obtained from JCPDS standard, d_{hkl} and 2θ values obtained from source material and from CdSe thin films, of $t = 2000\text{\AA}$, grown at different, T_s as well as from CdSe thin films of different, t , deposited at same $T_s = 473\text{K}$, corresponding to different lattice planes	95
3.3 Calculated values of structural parameters of CdSe thin films, of constant $t = 2000\text{\AA}$, deposited at different, T_s and of CdSe thin films, of different, t , deposited at constant $T_s = 473\text{K}$	98
CHAPTER IV	
Optoelectronic Properties of CdSe Thin Films	114-160
4.1(a) Calculated values of Poole-Frenkel coefficients (β_{PF}) in $10^4 \text{ eV V}^{-1/2} \text{ m}^{1/2}$ units for a CdSe film of $t = 2000\text{\AA}$ and grown at $T_s = 473\text{K}$, illuminated by different monochromatic lights	129
4.1(b) Calculated values of Poole-Frenkel coefficients (β_{PF}) in $10^4 \text{ eV V}^{-1/2} \text{ m}^{1/2}$ units for CdSe thin films of different thickness and grown at different T_s illuminated by monochromatic light of 725nm	133
4.2(a) Activation energies in dark (ΔE_D) under illumination (ΔE_L) & mobility activation (ΔE_μ) energies for a CdSe thin film ($t = 2000\text{\AA}$, $T_s = 473\text{K}$) in temperature regions R-I (360 to 453K) and R-II (300 to 360K)	146
4.2(b) Dark activation energy (ΔE_D) in eV of CdSe thin films of different thickness and grown at different T_s in temperature regions R-I (360 to 453K) and R-II (300 to 360K)	146

CHAPTER V

Spectral Response, Rise & Decay of Photocurrent and Optical Properties 161-205

- 5.1(a) Calculated values of σ , N_{eff} , S and E of a CdSe thin film ($t = 2000\text{\AA}$, $T_s = 473\text{K}$) under different monochromatic illuminations 182
- 5.1(b) Calculated values of σ , N_{eff} , S and E of a CdSe film ($t = 2000\text{\AA}$, $T_s = 473\text{K}$) under different monochromatic illuminations and applied bias conditions 182
- 5.2(a) Calculated values of σ , N_{eff} , S and E of a CdSe thin film ($t = 2000\text{\AA}$, $T_s = 473\text{K}$) under different white light illuminations, at room temperature 300K 182
- 5.2(b) Calculated values of σ , N_{eff} , S and E of a CdSe film ($t = 2000\text{\AA}$, $T_s = 473\text{K}$) under different white light illuminations, at room temperature 300K 183
- 5.2(c) Calculated values of σ , N_{eff} , S and E of a CdSe film ($t = 2000\text{\AA}$, $T_s = 473\text{K}$) under different white light illuminations, at an ambient temperature 333K 183
- 5.2(d) Calculated values of σ , N_{eff} , S and E of a CdSe film ($t = 2000\text{\AA}$, $T_s = 473\text{K}$) under different white light illuminations, at an ambient temperature 363K 183
- 5.3 Values of refractive index, n , absorption coefficient, α , and extinction coefficient, k , of a CdSe thin film of $t = 4950\text{\AA}$ and grown at $T_s = 523\text{K}$ at selected wavelengths 200
- 5.4 Optical band gap (E_g) values of CdSe thin films deposited at different T_s and of different thickness (t) 201